# DUMONDE PRO X BICYCLE CHAIN LUBE

Approval Date
Supersedes Date

09/01/2014

None

# Material Safety Data Sheet

Section I. Chemical Product and Company Identification **Product Product Name/** PX6001-6006 **Dumonde PRO X Bicycle Chain Lube Lite and Regular** ID No. **Trade Name Emergency Contact Dumonde Design Group Inc.** Supplier For Chemical Emergency, Spill, Leak, Fire, Exposure or Accident, Call P.O. BOX 3262 NORTH AMERICA 206-755-1757 KIRKLAND, WASHINGTON 98083-3262 Non-Emergency 206-755-1757 Synonym(s) Contact **Product Description** Hydrocarbons **USA: HGNR** 888-609-4467

Chemical Formula Mixture

Material Uses Bicycle Chain Lubricant

Section II. Composition and Information on Ingredients						
NAME	PEL/TLV, Source	CAS#	Concentration%	LVP-VOC/VOCs		
HYDRO TREATED MIDDLE DISTILLATE (PETROLEUM)		64742-46-7	10-25	Exempt		
PROPRIETARY FORMULA		PROPRIETARY	25-42	Exempt		
PROPRIETARY FORMULA		PROPRIETARY	4-18	<3%		
PROPRIETARY FORMULA		PROPRIETARY	20-42	Exempt		

LC <sub>50</sub>, LD <sub>50</sub> **of Ingredients** Not available

Section III. Hazards Identification

**Emergency Overview** Potential health risks vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be

minimized.

**Potential Health Effects:** 

**Eye Contact** May cause slight irritation and redness.

**Skin Contact** Prolonged or repeated skin contact may cause mild irritation.

IRRI

RITATION

HEALTH
REACTIVITY
PERSONAL PROTECTION

**Ingestion** While this product has a low degree of toxicity, ingestion may cause irritation of the digestive tract.

**Inhalation** Not expected to present an inhalation exposure risk at ambient temperatures. If vapors or mists are created upon heating or by

mechanical means, vapors or mists may be produced which may cause irritation of the breathing passages. Aspiration may

cause pulmonary edema or aspiration pneumonia.

### Section XI. Toxicological Information (cont'd)

Teratogenic Effects No data available to indicate any components present at greater than 0.1% may present a teratogenic hazard.

Reproductive Effects No data available to indicate any components present at greater than 0.1% may present a reproductive hazard.

## Section XII. Ecological Information

Ecotoxicity There is no data available on the adverse effects of this material on the environment.

### Section XIII. Disposal Considerations

Waste Disposal Consult federal, state or local authorities for proper disposal and reporting procedures. All disposals must comply with federal,

state and local regulations.

## Section XIV. Transportation Information

LAND (DOT): Not Regulated for Land
LAND (TDG): Not Regulated for Land

SEA (IMDG): Not Regulated for Sea Transport according to IMDG-Code

AIR (IATA): Not Regulated for Air Transportation

## Section XV. Regulatory Information

U.S. Federal Regulations:

CERCLA

These materials are not subject to any speacial reporting under the requiremments of the Coprehensive

Environmental Response, Compensation and Liability Act (CERCLA)

SARA (Section 313) These materials are not subject to any speacial reporting under the requiremments of the SARA (section 313)

SARA Extremely Hazardous List This product contains greater than 1.0% of the following chemical(s) on the SARA Extremely Hazardous Substances List:

None

**TSCA Inventory** All components of this material are on the U.S. TSCA Inventory.

California Prop. 65 This product contains the following chemical(s) known to the State of California to cause birth defects or other reproductive

harm:

None

#### International Regulations:

Canada All components are in compliance with the Canadian Environmental Protection Act. This product has been classified in

accordance with the hazard criteria of the CPR and this MSDS contains all the information required by CPR.

Japan MITINot availableAustraliaNot availableSwitzerlandNot available

### Section XVI. Other Information

Approval Date 09/01/2014 Supersedes Date NONE

Prepared by Dumonde Design Group Inc. 206-755-1757

Sections Revised Since Last Version

#### Section III. Hazards Identification (cont'd)

HMIS Code Health: 1 Fire: 1 Physical Hazard: 0 HAZARD RATINGS

1 Serious Hazard
1 Slight Hazard
2 Moderate Hazard
2 Moderate Hazard

### Section IV. First Aid Measures

Eye Contact Remove contact lenses, if wearing, and flush eyes with water. If irritation persists, consult a physician.

**Skin Contact** Remove clothing and shoes, if contaminated. Wash skin with soap and water. Wash or clean contaminated clothing before

reuse and discard oil-soaked shoes. If irritation persists, consult a physician. If high pressure forces the product under the

skin, get immediate medical attention!

**Ingestion** If swallowed, DO NOT induce vomiting. As a precaution, give the person a glass of water to drink and seek medical attention.

Never give anything by mouth to an unconscious person. Consult a physician.

Inhalation If exposed to excessive levels of material in the air, move the exposed person to fresh air. Seek medical attention if coughing or

respiratory discomfort occurs.

#### Section V. Fire and Explosion Data

Autoignition Temperature Not available Sensitivity to Impact Not available

Flash Point 118 °C (244 °F) Sensitivity to Static Discharge Not available

Flammable Limits (Approx.) LOWER Flammable Limit: Not available UPPER Flammable Limit: Not available

**Explosion Hazards** See Lower and Upper Flammable Limits

Products of Combustion Carbon monoxide, carbon dioxide, and as irritating smoke vapors products of incomplete combustion.

#### Fire Fighting Media Instructions

Dry chemical, alcohol foam, and carbon dioxide type extinguishing agents may all be suitable for extinguishing fires involving this type of product, depending on the size or potential size of fire and circumstances related to the situation. Plan fire protection and response strategy through consultation with local fire protection authorities or appropriate specialists. The following procedures for this type of product are based on the recommendations in the National Fire Protection Association's Fire Protection Guide on Hazardous Materials. Use water to keep fire-exposed containers cool. If a leak or spill has not ignited, use water spray to disperse the vapors and to provide protection for men attempting to stop a leak. Water spray may be used to flush spills away from explosives. Firefighters should wear full protective gear, including helmet. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

Special Remarks -Fire and Explosion Hazards For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus. Leaks/ruptures in high-pressure systems using materials of this type can create a fire hazard when in the vicinity of ignition sources (open flame, pilot lights, sparks or electric arcs).

## Section VI. Accidental Release Measures

Release or Spill Remove sources of ignition. Recover free product. Add sand, earth, or other suitable absorbent material to the spill area.

Minimize breathing vapors. Minimize skin contact. Open all windows and doors. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if the product has entered or may enter sewers, watercourses, or extensive land areas.

Environmental Impact Report spills as required to the appropriate authorities. U.S Coast Guard Regulations require immediate reporting of spills that

could reach any waterway including intermittent dry creeks. Report spill to the Coast Guard toll-free number 800-424-8802.

## Section VII. Handling and Storage

**Handling**Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force.

"Empty" containers retain product residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition as they may explode and can cause injury or death. Empty container should be promptly returned to a drum reconditioner. Electrically bond and ground all

containers and equipment.

Storage Do not use in high-pressure systems in the vicinity of flames, sparks, and hot surfaces. Keep container closed. Store in a cool, dry place. Do not store near heat, sparks, open flame, pilot lights, static electricity, or where temperature may exceed 120°F (49°C).

Keep out of reach of children.

## Continued on Next Page

# DUMONDE PRO X BICYCLE CHAIN LUBE

Approval Date
Supersedes Date

09/01/2014

None

# Material Safety Data Sheet

Section I. Chemical Product and Company Identification **Product Product Name/** PX6001-6006 **Dumonde PRO X Bicycle Chain Lube Lite and Regular** ID No. **Trade Name Emergency Contact Dumonde Design Group Inc.** Supplier For Chemical Emergency, Spill, Leak, Fire, Exposure or Accident, Call P.O. BOX 3262 NORTH AMERICA 206-755-1757 KIRKLAND, WASHINGTON 98083-3262 Non-Emergency 206-755-1757 Synonym(s) Contact **Product Description** Hydrocarbons **USA: HGNR** 888-609-4467

Chemical Formula Mixture

Material Uses Bicycle Chain Lubricant

Section II. Composition and Information on Ingredients						
NAME	PEL/TLV, Source	CAS#	Concentration%	LVP-VOC/VOCs		
HYDRO TREATED MIDDLE DISTILLATE (PETROLEUM)		64742-46-7	10-25	Exempt		
PROPRIETARY FORMULA		PROPRIETARY	25-42	Exempt		
PROPRIETARY FORMULA		PROPRIETARY	4-18	<3%		
PROPRIETARY FORMULA		PROPRIETARY	20-42	Exempt		

LC <sub>50</sub>, LD <sub>50</sub> **of Ingredients** Not available

Section III. Hazards Identification

**Emergency Overview** Potential health risks vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be

minimized.

**Potential Health Effects:** 

**Eye Contact** May cause slight irritation and redness.

**Skin Contact** Prolonged or repeated skin contact may cause mild irritation.

IRRI

RITATION

HEALTH
REACTIVITY
PERSONAL PROTECTION

**Ingestion** While this product has a low degree of toxicity, ingestion may cause irritation of the digestive tract.

**Inhalation** Not expected to present an inhalation exposure risk at ambient temperatures. If vapors or mists are created upon heating or by

mechanical means, vapors or mists may be produced which may cause irritation of the breathing passages. Aspiration may

cause pulmonary edema or aspiration pneumonia.